



HYDROMASK HS2

Fountain Solution for Heatset Offset

DESCRIPTION

Fountain solution particularly suitable for HEATSET. It provides high cleaning ability, a plugged pH values between 4.70 and 5.00% depending on the addition and the water hardness. Powerful biocide effect. To print between 0% and 4% alcohol.

APPLICATIONS

- Offset Rotary machine Heat set (Commercial)
- Suitable for all dampening systems.
- For printing with conventional inks.

PROPERTIES

- Good ink-water balance.
- Starts fast printing.
- Low water consumption
- For water with hardness between 5 and 18 ° dH.
- Minimizes the accumulation of ink and paper fiber on the rubber
- Contains corrosion inhibitors

SPECIFICATIONS

Color	Green
Density	1,080 g/cc
Plugged values	pH 4,7 – 5,00
Conductivity for 1%	540 ms
Dosification	2,5-4%

STORAGE

Do not expose to temperatures below 5°C or up to 35°C. Expiration 24 months for closed package and under correct temperature conditions.

PACKAGING

Drum 20 Kg./ Drum 220 Kg. / Container 1000 Kg.

HOW TO USE

We advise to add according to the hardness of the water the following percentages of additive. A more water hardness more % amount of additive.

The values are illustrative, adjusting them according to the specific needs of the environment.

