



KAUSTIMASK S

Cleaner and conditioner paste of screens

DESCRIPTION

Cleaning paste caustic based, for cleaning and conditioning of frames and meshes of the screens.

APPLICATIONS

- Printing screen mesh

PROPERTIES

- Great cleaning power.
- Degreaser, the screens get ready to coat.

SPECIFICATIONS

Color
Physical Form
Corrosive

Beige
Paste
Yes

STORAGE

Do not expose to temperatures below 5°C or up to 40°C. Expiration 24 months for closed package and under correct temperature conditions.

PACKAGING

Box 12 Kg (12 x 1Kg.) / Box 20 Kg (4 x 5 Kg.)

HOW TO USE

- 1 To clean and condition new and used meshes: rub with a brush of both sides of mesh. Leave settle for a moment and wash thoroughly with abundant water. The mesh will be ready to be coated.
- 2 To condition and prepare metal frames for perfect mesh adhesion. Rub with a brush the frame until dirt disappears. Leave the product work and wash thoroughly with abundant water.
- 3 To eliminate ink or emulsion leftovers and ghost image after emulsion elimination. Combine KAUSTIMASK S with DISOLIX GEL at 1:1 over the screen and rub with a brush both sides of mesh, and let it act depending on the intensity of the residue to remove.

