



# KOPIMASK

Technical Information

TDS

## PROTEC ROL

No friction lubricant for printing unit rollers

### DESCRIPTION

No friction lubricant to be used on running IDLE rollers, in non-printing units.

### SPECIFICATIONS

Color  
Aspect  
Solubility in water

Brownish  
Oily  
No

### STORAGE

Do not expose to temperatures below 5°C or up to 35°C. Expiration 24 months for closed package and under correct temperature conditions.

### PACKAGING

Box 20 L. (20 x 1L). / Box 4 L. (4 x 1L.)

### HOW TO USE

Apply the enough quantity to have a good distribution between the cylinders.

Prolonged use does not damage the cylinders and makes them easier to wash later.



1

D09.04/1 F8C3 17/01/2024

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.

KOPIMASK, S.A. Industria, 28 - 08184 Palau Solità I Plegamans - Barcelona - España - Tel. 00 34 938639350 - support@kopimask.eu