



TDS

# KOPIMASK

## Technical Information

# GEL FARLUX

Anti repaint conditioner

### DESCRIPTION

Anti-repaint conditioner for offset inks formulated to softens the ink on the ink rollers and improves drying on the printed sheet by thixotropic action.

### APLICACIONES

- Under-printing.
- Printing on metallic inks.
- Printing on couche paper.
- Printing on recycled papers.
- Printing on vegetal papers.
- Printing on paper board.

### PROPERTIES

- Improve drying
- Reduce repainting.
- Reduce anti set powders
- Ink save
- More intense colors
- More gloss

### SPECIFICATIONS

Color  
Physical form  
Flammable

White  
Paste  
No

### STORAGE

Do not expose to temperatures below 5°C or up to 35°C. Expiration 24 months for closed package and under correct temperature conditions.

### PACKAGING

Box 12 L (12 x 1L)

### HOW TO USE

1



D09.04/1 F8C2 17/07/2023

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.

**KOPIMASK, S.A.** Industria, 28 - 08184 Palau Solità I Plegamans - Barcelona - España - Tel. 00 34 938639350 - support@kopimask.eu



TDS

# KOPIMASK

## Technical Information

### GEL FARLUX

#### Anti repaint conditioner

---

- 1 Add between 2% and 3% of **GEL FARLUX** into the ink (20 – 30 gr./Kg.)
- 2 Shake/mix until the total incorporation with the ink.
- 3 It is not recommended to exceed the 4%.

