



KOPIMASK

Technical Information

TDS

SERI CERO DRY

Powder Stripper

DESCRIPTION

Powder stripper (must mixed with water) to eliminate the emulsions from screening frames. Fast action.

APLICATIONS

- Eliminate emulsion from screening frames.
- Does not eliminate catalyzed emulsions or chemically hardened.

PROPIERTIES

- Good stripping powder.
- Degreaser, the screens get ready to be coated.

SPECIFICATIONS

Color	White
Odor	Odorless
Aspect	Solid powder
Irritant	Yes

STORAGE

Do not exposure to temperatures below of 0°C or up to 45°C. The product is sensitive to frosts.

PACKAGING

50 gr. / 1 kg. / 25 kg.

HOW TO USE

Dilute the doses of 50 gr. SERI CERO DRY in 10 liters of water.

Apply both sides of the coated screen with a brush, leave 5 minutes and rinse with pressure water.

In case of hard emulsions, dilute the doses of 50 gr. between 7 – 8 litres of water, to get a more energetic stripping.



1

D09.04/1 F8C3 07/06/2023

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.

KOPIMASK, S.A. Industria, 28 - 08184 Palau Solità I Plegamans - Barcelona - España - Tel. 00 34 938639350 - support@kopimask.eu